

B806 ALU

THE SUCCESS OF THE SMALL B806 IN REINFORCED ALUMINIUM

Bollé Safety offers a simple and flexible system, based on a unique pricing. The RX range is composed of a wide range of frames that can be glazed with 3 types of prescription lenses (single vision, bifocal, progressive) and 3 different lens materials (polycarbonate, CR39 or toughened glass).



Ref. B806 ALU



30 g

SUPPLIED WITH

Hard case,
microfibre cloth,
cord



FRAME

• Aluminium

LENS MATERIAL AVAILABLE

• CR39
• Polycarbonate

+ UPPER, LOWER AND SIDE PROTECTION

+ ALUMINIUM FRAME

+ FIXED SIDE SHIELDS

+ ADJUSTABLE PADS

bolle
SAFETY

B806 ALU

THE SUCCESS OF THE SMALL B806 IN REINFORCED ALUMINIUM

MODEL	VERSIONS	REFERENCES	SIZE	FRAME MARKING	TEMPLE LENGTH
B806 ALU	Aluminium / Smoke	B806 ALU	54/17	 EN166 F C€	132 mm

LENS MARKING

Lens available in clear, 3 shades of gray and 3 shades of smoke.

Polycarbonate lens:

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

CR39 lens:

S. Extra strong, resists a 22 mm 43 g ball falling 1.30 m at 5,1 m/s.

FRAME MARKING

EN 166 : guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

C€ European standard  Manufacturer name

Bollé safety product approval certificates to CE standards will be sent on request.

STANDARD ASSEMBLY RESTRICTIONS:

Maximum sphere power +8/-8.

Maximum cylinder compared with sphere : +/-6.

CORRECTED BASE:

Corrected base : 4

CLEANING AND STORAGE

CLEANING : The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE : Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE : All products must be stored in a dry and clean environment.

PACKAGING AND EAN13 CODE	
	B804
Per piece	3660740000318

CHARACTERISTICS	
LENS	CR39, Polycarbonate
TYPES OF CORRECTIONS AVAILABLE	Single vision - Bifocal - Progressive
FRAME	Aluminium / Smoke
STRAP	Non applicable
FOAM	Non applicable



Europe Bollé Safety
95 rue Louis Guérin
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : sales@bolle-safety.co.uk

14/01/2014

bolle
SAFETY