

# MACRO

**TRENDY DESIGN AND PIVOTING TEMPLES TO ADAPT THE COVERING SURFACE OF THE GLASSES**

Bollé Safety offers a simple and flexible system, based on a unique pricing. The RX range is composed of a wide range of frames that can be glazed with 3 types of prescription lenses (single vision, bifocal, progressive) and 3 different lens materials (polycarbonate, CR39 or toughened glass).



Ref. MACN



19 g

#### SUPPLIED WITH

Hard case,  
microfibre cloth,  
cord



#### FRAME

• TR90 + PC

#### LENS MATERIAL AVAILABLE

- CR39
- Polycarbonate
- Toughened glass

**+ IN-BUILT SIDE SHIELDS**

**+ PIVOTING TEMPLES**

**+ UPPER PROTECTION**

**bollé**  
SAFETY

# MACRO

TRENDY DESIGN AND PIVOTING TEMPLES TO ADAPT THE COVERING SURFACE OF THE GLASSES

MODEL	VERSIONS	REFERENCES	SIZE	FRAME MARKING	TEMPLE LENGTH
MACRO	Clear blue Grey	MACN	54/18	EN166 F C€	140 mm

## LENS MARKING

Lens available in clear, 3 shades of gray and 3 shades of smoke.

### Polycarbonate lens:

**F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.


### CR39 and toughened glass lens:

**S.** Extra strong, resists a 22 mm 43 g ball falling 1.30 m at 5,1 m/s.

## FRAME MARKING

**EN 166** : guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

**F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.

C€ European standard  Manufacturer name

**Bollé safety product approval certificates to CE standards will be sent on request.**

## STANDARD ASSEMBLY RESTRICTIONS:

**Maximum sphere power +6/-6.**

**Maximum cylinder compared with sphere : +/-3.**

## CORRECTED BASE:

**Corrected base : 6**

## CLEANING AND STORAGE

**CLEANING** : The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

**MAINTENANCE** : Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE** : All products must be stored in a dry and clean environment.

PACKAGING AND EAN13 CODE	
	MACN
Per piece	3660740004088

CHARACTERISTICS	
LENS	CR39, Polycarbonate, Toughened glass
TYPES OF CORRECTIONS AVAILABLE	Single vision - Bifocal - Progressive
FRAME	Clear blue grey
STRAP	Non applicable
FOAM	Non applicable



Europe Bollé Safety  
95 rue Louis Guérin  
69100 Villeurbanne - France  
Tél. : 00 33 (0) 4 78 85 23 64  
Fax : 00 33 (0) 4 78 85 28 56  
contact@bolle-safety.com

[bolle-safety.com](http://bolle-safety.com)

U.K. Bollé Safety  
Unit C83 - Barwell Business Park Leatherhead Road - Chessington  
Surrey - KT9 2NY  
Tél. : 00 44 (0)208 391 4700  
Fax : 00 44 (0)208 391 4733  
e-mail : sales@bolle-safety.co.uk

22/01/2018

**bolle**  
SAFETY